



- ◆ 5 x 7 DOTS WITH CURSOR
- ◆ BUILT-IN CONTROLLER (KS0066 OR EQUIVALENT)
- ◆ 5 V POWER SUPPLY
- ◆ 1/16 DUTY CYCLE
- ◆ 4.2 V LED FORWARD VOLTAGE

MECHANICAL DATA

ITEM	DIMENSIONS	UNIT
Module Size (W x H x T)	53.0 x 20.0 x 8.0	mm
Viewing Area (W x H)	36.0 x 10.0	mm
Character Size (W x H)	1.85 x 3.15	mm
Character Pitch (W x H)	2.15 x4.25	mm
Dot Size (W x H)	0.33 x 0.35	mm
Dot Pitch (W x H)	0.38 x 0.40	mm


■ INTERFACE PIN CONNECTIONS

NO.	SYMBOL	FUNCTION	NO.	SYMBOL	FUNCTION
1	V _{SS}	Supply Ground	9	DB2	Data Bit 2
2	V _{DD}	Supply Voltage	10	DB3	Data Bit 3
3	V _O	Contrast Adj.	11	DB4	Data Bit 4
4	RS	Register Select	12	DB5	Data Bit 5
5	R/W	Read/Write	13	DB6	Data Bit 6
6	E	Enable Signal	14	DB7	Data Bit 7
7	DB0	Data Bit 0	15	A	LED Power
8	DB1	Data Bit 1	16	K	LED Power

■ ELECTRICAL CHARACTERISTICS

ITEM		SYMBOL	CONDITION	MIN.	TYP.	MAX.	UNIT
LCD Operating Voltage		V _{DD-Vo}	T=0℃	-	4.8	-	V
			T=25℃	-	4.5	-	V
			T=50℃	-	4.2	-	V
Supply Voltage		V _{DD-VSS}	-	4.7	5	5.3	V
Supply Current		I _{DD}	-	-	2	4	mA
Input	"HIGH" Level	V _{IH}	-	2.2	-	V _{DD}	V
Voltage	"LOW" Level	V _{IL}	-	0	-	0.6	V
Output	"HIGH" Level	V _{OH}	-	2.4	-	-	V
Voltage	"LOW" Level	V _{OL}	-	-	-	0.4	V

■ BLOCK DIAGRAM



EXTERNAL DIMENSIONS

