

SG19232B (192 DOTS X 32 DOTS)

FEATURES

- ◆ BUILT-IN CONTROLLER (SED1520 OR EQUIVALENT)
- ◆ +5 V POWER SUPPLY
- ◆ 1/32 DUTY CYCLE
- ◆ 8-BIT PARALLEL INTERFACE
- ◆ 4.2 V LED FORWARD VOLTAGE

MECHANICAL DATA

ITEM	DIMENSIONS	UNIT
Module Size (W x H x T)	116.0 x 37.0 x 9.4 (10.8 LED)	mm
Viewing Area (W x H)	88.0 x 19.0	mm
Active Area (W x H)	80.6 x 16.28	mm
Dot Size (W x H)	0.38 x 0.47	mm
Dot Pitch (W x H)	0.42 x 0.51	mm

INTERFACE PIN CONNECTIONS

NO.	SYMBOL	LEVEL	FUNCTION
1	Vss	0V	Power Supply Ground
2	VDD	5V	Power Supply Voltage
3	Vo	-	Contrast Adjustment Voltage
4	Ao	H/L	Data Type Select Signal
5	R/W	H/L	H : Read / L : Write
6	E	H→L	Enable Signal
7~14	DB0~DB7	H/L	Data Bus Line
15	A	4.2V	LED Power (+)
16	K	0V	LED Power (-)
17	CS1	H	Chip Select Signal For IC1
18	CS2	H	Chip Select Signal For IC2
19	CS3	H	Chip Select Signal For IC3
20	CL	H/L	Clock Input (2 KHz)


ABSOLUTE MAXIMUM RATINGS


ITEM	SYMBOL	MIN.	TYP.	MAX.	UNIT
Supply Voltage For Logic	VDD-Vss	0	-	7	V
Supply Voltage For LCD Drive	VDD-Vo	0	-	12	V
Input Voltage	Vi	Vss	-	VDD	V

ELECTRICAL CHARACTERISTICS

ITEM		SYMBOL	CONDITION	MIN.	TYP.	MAX.	UNIT
Supply Voltage For Logic		VDD-VSS	-	4.5	5	5.5	V
Supply Voltage For LCD		VDD-V _o	VDD=5V Ta=25℃	4.4	4.8	5.2	V
Supply Current		IDD	VDD=5V	-	3	4.5	mA
Input	"HIGH" Level	VIH	-	2.2	-	VDD	V
Voltage	"LOW" Level	VIL	-	-	-	0.6	V
Output	"HIGH" Level	VOH	-	2.4	-	-	V
Voltage	"LOW" Level	VOL	-	-	-	0.4	V

EXTERNAL DIMENSIONS






SG19232B (192 DOTS X 32 DOTS)

TIMING CHARACTERISTICS

ITEM		SYMBOL	MIN.	TYP.	MAX.	UNIT.
System Cycle Time		t_{CYC6}	1000	-	-	ns
Address Set-up Time		t_{AW6}	20	-	-	ns
Address Hold Time		t_{AH6}	10	-	-	ns
Data Set-up Time		t_{DS6}	80	-	-	ns
Data Hold Time		t_{DH6}	10	-	-	ns
Output Disable Time		t_{OH6}	10	-	60	ns
Access Time		t_{ACC6}	-	-	90	ns
Enable Pulse Width	Read	t_{EW}	100	-	-	ns
	Write		80	-	-	ns



BLOCK DIAGRAM

